



KelairPumps

Standard Duty

Sandpiper Air-Operated Diaphragm Pumps



MODEL	PB¼ Non-Metallic	S05 Non-Metallic	S05 Metallic	S07 Non-Metallic	S10 Non-Metallic	S1F Non-Metallic
Max. Flow LPM	15	52	56	87	87	200
Max. Discharge Pressure Bar	7.0	7.0	7.0	7.0	7.0	7.0
Fluid Ports Inlet/Outlet	¼" NPT(F)	½" BSP(F)	½" BSP(F)	¾" BSP(F) 1½" BSP(F)	1" ANSI Flange	1" ANSI Flange
Materials of Construction	Polypropylene Kynar Conductive Acetal	Polypropylene Kynar Conductive Acetal Nylon	Aluminium 316 SS	Polypropylene Kynar Conductive Acetal Nylon	Polypropylene Kynar Conductive Acetal Nylon	Polypropylene Kynar Conductive Acetal Nylon
Pump Weight kg	Polypropylene-2kg Kynar-2kg	Polypropylene-9kg Kynar-9kg	Aluminium-6kg 316SS-11kg	Polypropylene-8kg Kynar-9kg	Polypropylene-9kg Kynar-9kg	Polypropylene-17kg Kynar-29kg
Maximum Solids mm	1.0	3.0	3.0	4.0	4.0	6.4



MODEL	S1F Metallic	S15 Non-Metallic	S15 Metallic	S20 Non-Metallic	S20 Metallic	S30 Non-Metallic	S30 Metallic
Max. Flow LPM	170	378	401	605	567	901	889
Max. Discharge Pressure Bar	7.0	7.0	7.0	7.0	7.0	7.0	7.0
Fluid Ports Inlet/Outlet	1" BSP(F)	1½" ANSI Flange	1½" BSP(F)	2" ANSI Flange	2" BSP(F)	3" ANSI Flange	3" BSP(F)
Materials of Construction	Aluminium Cast Iron 316 SS	Polypropylene Kynar	Aluminium Cast Iron 316 SS	Polypropylene Kynar	Aluminium Cast Iron 316 SS	Polypropylene Kynar	Aluminium Cast Iron 316 SS
Pump Weight kg	Aluminium-13kg Cast Iron-21kg	Polypropylene-29kg Kynar-35kg	Aluminium -24kg Cast Iron-42 316SS-43kg	Polypropylene-34kg Kynar-68kg	Aluminium-35kg Cast Iron-60kg 316SS-54kg	Polypropylene-105g Kynar-143kg	Aluminium-53kg Cast Iron-103kg 316SS-110kg
Maximum Solids mm	6.0	12.0	6.0	17.0	6.0	18.0	9.5

Kelair Pumps Australia Pty Ltd Gateway Estate 215 Walters Road Arndell Park NSW 2148
Call Direct: 1300 789 466 Fax: 02 9678 9455 ABN 28 001 308 381
E: kelair@kelairpumps.com.au www.kelairpumps.com.au

SPISD-4c-0308

